



US010892044B2

(12) **United States Patent
Fisher**

(10) **Patent No.: US 10,892,044 B2**

(45) **Date of Patent: Jan. 12, 2021**

(54) **CONNECTED MEDICAL DEVICES**

(71) Applicant: **Michelle T Fisher**, Marina Del Rey, CA (US)

(72) Inventor: **Michelle T Fisher**, Marina Del Rey, CA (US)

(73) Assignee: **Michelle Fisher**, Berkeley, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 465 days.

(21) Appl. No.: **14/078,440**

(22) Filed: **Nov. 12, 2013**

(65) **Prior Publication Data**

US 2015/0134358 A1 May 14, 2015

US 2018/0144096 A9 May 24, 2018

Related U.S. Application Data

(63) Continuation of application No. 13/218,879, filed on Aug. 26, 2011, which is a continuation-in-part of application No. 13/216,098, filed on Aug. 23, 2011, now abandoned, which is a continuation-in-part of application No. 13/215,069, filed on Aug. 22, 2011, now abandoned, which is a continuation-in-part of application No. 13/213,840, filed on Aug. 19, 2011, (Continued)

(51) **Int. Cl.**

G16H 10/60 (2018.01)

G16H 10/65 (2018.01)

G06F 19/00 (2018.01)

(52) **U.S. Cl.**

CPC **G16H 10/60** (2018.01); **G06F 19/00** (2013.01); **G16H 10/65** (2018.01)

(58) **Field of Classification Search**

CPC G06Q 50/22; G06Q 50/24; G16H 10/60
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0130708 A1 * 7/2003 Von Arx A61N 1/08
607/60

2005/0222933 A1 * 10/2005 Wesby G06Q 40/00
705/36 R

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 2006108858 A1 * 10/2006 G06F 8/60

OTHER PUBLICATIONS


Smart Card Alliance Report, Smart Cards and Biometrics in Privacy-Sensitive Secure Personal Identification Systems, Smart Card Alliance, May 2002, ID-02001 (Year: 2002).*

Primary Examiner — Evangeline Barr

(57) **ABSTRACT**

This invention describes how users can capture digital artifacts from any medical device using their mobile device. Some examples of medical devices included, but are not limited to a medical ID card, Medical ID bracelet, Electronic Medical Records, blood pressure machines, blood glucose, scales, inhalers, INR, prescription bottles and trays, pulse oximeter, etc. Digital artifacts included, but are not limited to a medical ID, basic patient information, patient contact information, emergency contact information, primary care physician information, health insurance information including co-pay and deductibles, prescriptions, office visit summary, appointment cards, Electronic Medical Records (EMR), lab results, blood type, organ/donor status, vital signs, diagnostic data, immunization records, payments and transaction history, pictures, etc.

39 Claims, 9 Drawing Sheets



Related U.S. Application Data

now abandoned, which is a continuation-in-part of application No. 13/208,247, filed on Aug. 11, 2011, now abandoned, which is a continuation-in-part of application No. 13/184,209, filed on Jul. 15, 2011, now abandoned.

- (60) Provisional application No. 61/442,384, filed on Feb. 14, 2011.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0025657	A1 *	2/2006	Rosenfeld	G16H 50/20 600/300
2006/0056655	A1 *	3/2006	Wen	G06F 19/3418 382/103
2007/0038516	A1 *	2/2007	Apple et al.	705/14
2007/0135866	A1 *	6/2007	Baker	A61B 5/0002 607/60
2008/0004009	A1 *	1/2008	Caldwell	H04L 29/12188 455/434
2009/0054737	A1 *	2/2009	Magar et al.	600/300
2009/0164253	A1 *	6/2009	Lyshkow	G06F 19/321 705/3
2009/0177495	A1 *	7/2009	Abousy et al.	705/3
2010/0152551	A1 *	6/2010	Hsu	A61B 5/0002 600/301
2011/0167133	A1 *	7/2011	Jain	H04L 67/12 709/219
2012/0185267	A1 *	7/2012	Kamen	G06Q 50/22 705/2
2014/0017990	A1 *	1/2014	Kakadia	H04W 36/14 455/7

* cited by examiner




Figure 1




Figure 2




FIG. 2B1




FIG. 2B2A




FIG. 2B2B




Figure 3





Figure 4



Cable 141

Figure 5




Figure 6

Health Care Secure Element Application ID	Function
SE_App1	Transfer medical ID to another NFC enabled device requiring authentication prior to transmission
SE_App2	Transfer medical ID to another NFC enabled device without authentication prior to transmission
SE_App3	Transfer prescriptions to another NFC enabled device requiring authentication prior to transmission
SE_App4	Purchase prescriptions using an NFC enabled device requiring authentication prior to transmission
SE_App5	Transfer EMR to another NFC enabled device requiring authentication prior to transmission
SE_App6	Transfer diagnostic data to another NFC enabled device requiring authentication prior to transmission
SE_App7	Transfer diagnostic data to another NFC enabled device without authentication prior to transmission
SE_App8	Transfer immunization and other shots to NFC enabled device with authentication prior to transmission
SE_App9	Transfer Xrays to NFC enabled device with authentication prior to transmission
SE_App10	Pay with contactless payment method such as Pay Pass
SE_App11	Get nutritional values from products
SE_App12	Get medical dosages from medicine container
SE_App13	Get appointment card
SE_App14	Basic Patient Info (e.g. blood type, birth date,etc)
SE_App15	Medical Conditions
SE_App16	Allergies
SE_App17	Emergency Contact Info
SE_App18	Medications
SE_App19	Health Plan Information
SE_App20	Dynamic Verification Code
SE_App21	Get blood pressure data
SE_App22	Register medical sensor

Figure 7




Figure 8

CONNECTED MEDICAL DEVICES

CLAIM OF PRIORITY

This application is a continuation in part and claims priority to U.S. patent application Ser. No. 13/218,879 entitled "Using an NFC Enabled Mobile Device To Manage Digital Medical Artifacts" filed on Aug. 26, 2011 which is a continuation in part and claims priority to U.S. patent application Ser. No. 13/216,098 entitled "Streamlining NFC Transactions Using A Mobile Communication Device" filed on Aug. 23, 2011 which is a continuation in part and claims priority to U.S. patent application Ser. No. 13/215,069 entitled "Transferring Data From an NFC Enabled Mobile Device to a Remote Device" filed on Aug. 22, 2011 which is a continuation in part of U.S. patent Ser. No. 13/213,840, entitled "Transferring Data Between NFC Enabled Mobile Devices With Multiple Secure Elements" filed on Aug. 19, 2011 which is a continuation in part and claims priority to U.S. patent Ser. No. 13/208,247, entitled "Transferring Data Between NFC Enabled Mobile Devices" filed on Aug. 11, 2011 which is a continuation in part of U.S. patent Ser. No. 13/184,209, entitled "Method and Systems of loading and unloading digital artifacts between a mobile device with an associated secure element and other remote devices" filed on Jul. 15, 2011 which claims priority to U.S. Provisional Patent Application No. 61/442,384, entitled "Method and Systems of loading and unloading digital between a mobile device with an associated secure element and other remote devices" filed on Feb. 14, 2011. All of the above-referenced patent applications are incorporated by reference herein in their entirety

RELATED APPLICATIONS

Other patents referenced include U.S. patent application Ser. No. 13/223,233, "Using an NFC Enabled Mobile Device To Manage Health Care" filed on Aug. 31, 2011, U.S. patent application Ser. No. 11/944,267, entitled "Method and System for Delivering Information to a mobile communication device based on consumer transactions", filed Nov. 21, 2007 and U.S. patent application Ser. No. 11/956,261 entitled "Method and System for Delivering Customized Information To A Mobile Communication Device Based on User Affiliations", filed Dec. 13, 2007. All of the above-referenced patent applications are incorporated by reference herein in their entirety

FIELD OF INVENTION

The present invention relates to data communications and wireless devices.

BACKGROUND OF THE INVENTION

Mobile communication devices—e.g., cellular phones, personal digital assistants, and the like—are increasingly being used to conduct payment transaction. Such payment transactions can include, for example, purchasing goods and/or services, tickets, bill payments, and transferring funds between bank accounts. Because of bigger screens, better user input with touch screens increased processing capability, and faster more reliable wireless mobile devices, can be used to manage electronic medical records.

BRIEF SUMMARY OF THE INVENTION

Medical devices capture and/or store data. Some examples of medical devices included, but are not limited to

a medical Identification (ID) card, Medical ID bracelet, Electronic Medical Records, blood pressure machines, blood glucose, scales, inhalers, INR, prescription bottles and trays, pulse oximeter, or any device that captures and stores medical data. However, medical devices don't export data or not very easily. So, the Health Care Provider (HCP) is required to manually write down the sensor/measurement data displayed on the medical device and/or enter it into a computer which is time consuming, prone to error, and costly.

While some medical devices have the ability to export data to a personal computer using a cable or wirelessly using Blue Tooth™ for example, these few devices have special customized interfaces which are costly and limit the patient and health care provider to using those devices which may not be their preferred medical device. In many instances patients and health care providers prefer to use certain medical devices based on their functionality, cost, or accuracy in capturing measurement data particularly for very serious chronic illnesses where accuracy is extremely important.

This invention describes various ways to capture data from any medical device and transmit it electronically to mobile devices (e.g. cell phones, smart phones, electronic note books), computers, servers, electronic medical records, etc. by using a secure element that serves as a "universal health port". Thus, making a solution that is more scalable, flexible, cost effective, and beneficial to patients, health care providers, etc.

This application is a continuation in part and claims priority to U.S. patent application Ser. No. 13/216,098 entitled "Streamlining NFC Transactions Using A Mobile Communication Device" filed on Aug. 23, 2011 which is a continuation in part and claims priority to U.S. patent application Ser. No. 13/215,069 entitled "Transferring Data From an NFC Enabled Mobile Device to a Remote Device" filed on Aug. 22, 2011 which is a continuation in part of U.S. patent Ser. No. 13/213,840, entitled "Transferring Data Between NFC Enabled Mobile Devices With Multiple Secure Elements" filed on Aug. 19, 2011 which is a continuation in part and claims priority to U.S. patent Ser. No. 13/208,247, entitled "Transferring Data Between NFC Enabled Mobile Devices" filed on Aug. 11, 2011 which is a continuation in part of U.S. patent Ser. No. 13/184,209, entitled "Method and Systems of loading and unloading digital artifacts between a mobile device with an associated secure element and other remote devices" filed on Jul. 15, 2011 which claims priority to U.S. Provisional Patent Application No. 61/442,384, entitled "Method and Systems of loading and unloading digital between a mobile device with an associated secure element and other remote devices" filed on Feb. 14, 2011. All of the above-referenced patent applications are incorporated by reference herein in their entirety

BRIEF SUMMARY OF THE INVENTION

The system is configured with a mobile device (with client application also referred to as a mobile wallet), a secure element that is associated with the mobile device, Near Field Communication (NFC) Point Of Sale System (POS) which is capable of processing financial transactions (including 2-way wireless terminal capable of sending and transmitting), NFC Point-Of-Presence (POP) Terminal which is capable of processing non-financial transactions (including 2-way wireless terminal capable of sending and transmitting), an NFC Point-of-Entry (POE) Device which is capable of providing access to venues including 2-way

wireless terminal capable of sending and transmitting, a management server, a Trusted Service Manager (TSM) and several 3rd Party artifact provider/aggregator.

In the delivery scenario, when the user holds an NFC enabled mobile communication device with a secure element coupled to it in proximity of a suitable equipped POS/POE/POP with NFC, the NFC POS/POE/POP device will trigger an application residing in the secure element (which is different than an application residing on the mobile communication device) to power on and activate an application residing in the secure element, transfer data or digital artifacts (e.g debit/prepaid/credit card, receipts, tickets, advertisements, coupons, loyalty points, gift cards, vouchers, content (video, image, ringtone, movie), games, documentation, business cards, tickets, hotel key, health care records, security key, automobile key, etc.) from/to the secure element, and the secure element may issue commands and/or respond to commands just to name a few. Using this system, at the time of a transaction, a user can use the mobile wallet software (on a mobile computing device) and associated secure element, in conjunctions with the POP/POS/POE to:

- Store medical ID
- Store patient contact information such as address, phone number, employer contact info
- Store emergency contact information
- Store basic patient information such as gender, age, date of birth, blood type, race, etc
- Store physician names and contact information
- Store allergies
- Store a list of vaccinations
- Store vital signs such as temperature, blood pressure, pulse, respiratory rate, "pain" level, glucose level, cholesterol, height, weight, etc
- Store insurance information including list of approved doctors approved labs, approved drugs, approved generic drugs, health care coverage, out of pocket costs, co-pay costs
- Payment methods—credit, debit, prepaid, checking account number
- Store prescriptions
- Store doctors' orders for use of prescriptions
- Pay for prescriptions
- Store XRays
- Store lab results
- Pay for lab tests
- Store hospital ID bracelet
- Store medication used in hospital
- Schedule of doctor appointments
- Store organ status and donor information
- Transfer digital medical artifacts (e.g medical ID, basic patient information, patient contact information, emergency contact information, primary care physician information, health insurance information including co-pay and deductibles, prescriptions, office visit summary, appointment cards, Electronic Medical Records (EMR), lab results, blood type, organ/donor status, vital signs, diagnostic data, immunization records, payments and transaction history, pictures, etc) to remote devices

Some of the challenges that an NFC enabled mobile device can address include, but are not limited to the following use cases:

Elderly/Senior Citizens—They may have a sudden health care need with a sensitive need to have a list of medical information, allergies, and prescriptions readily available for urgent health care. Care givers may not have access to their medical information.

ER Patients Their identity may not be known when they arrive at ER and require emergency medical treatment. So, it is urgent to identify who they are, medical history, allergies, and prescriptions, etc.

New Patients—If a new patient is visiting a new doctor for a diagnosis and potentially time sensitive, treatment, patients will need to have medical information, allergies, and prescriptions readily available which may take weeks to receive from previous physician.

Children—Children may not have an ID with them and be on a field trip, sporting event, camping trip, friend's house, etc. So, if there is a health issue, it will be important to be able to confirm their identity, medical information, allergies, and prescriptions readily available for urgent health care, etc.

Frequent international travelers—Frequent travelers need to track their shots and immunizations for travel abroad. If they may have a sudden health care need, they will need to have access to medical information, allergies, and prescriptions readily available for urgent health care.

Patients with Alzheimer's or other conditions that impact memory. They may get lost and not remember who they are or how to get back home or have any identification with them. So, they health care professionals will need to be able to identify them as well as their medical history, allergies, and prescriptions readily available for urgent health care.

Critically serious patients in ICU or prenatal may have require very specific medications and dosages.

Patients who require daily or constant monitoring for insulin levels, asthma, high blood pressure, heart pace maker, etc.

This invention enables patients and health care professionals (nurse, doctor, pharmacist, etc) to manage digital medical artifacts medical digital artifacts (e.g. medical ID, basic patient information, patient contact information, emergency contact information, primary care physician information, health insurance information including co-pay and deductibles, prescriptions, office visit summary, appointment cards, Electronic Medical Records (EMR), lab results, blood type, organ/donor status, vital signs, diagnostic data, immunization records, payments and transaction history, pictures, etc) using an NFC enabled mobile device. This is accomplished when the user holds, "waves", or "taps" their NFC enabled device in proximity to an NFC Point-Of-Presence (POP) device, Point-Of-Entry (POE), Point-Of-Sale (POS) device, smart poster, or another NFC enabled device. Upon doing so, the POP/POE/POS/etc activates the secure element associated with the NFC enabled mobile device and powers the secure element through induction. So, the secure element need not have its own power source nor does the secure element require use of the battery inside of the mobile device. Correspondingly, if the battery in the mobile device is dead, the user may not be able to use the mobile device to place a phone call, receive an SMS, or surf the web, but they will be able to transfer information from their secure element (e.g. medical ID) since the secure element is powered by the remote NFC enabled POP/POS/POE device. The secure element can also receive digital artifacts from a POP/POS/POE device such as Xrays, prescriptions, appointment cards, etc even if the battery inside of the mobile communication device lacks power. This communication is specified, for example, in the ISO 14443A/B standard and ISO 15693 just to name a few.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of a communication system including a wireless mobile communication device and a management server in accordance with one implementation.

5

FIG. 2 illustrates a block diagram of a mobile communication device in accordance with one implementation.

FIG. 3 illustrates a block diagram of a secure element in accordance with one implementation.

FIGS. 2B1, 2B2A, 2B2B illustrate more details regarding certain components illustrated in FIG. 1.

FIG. 3 illustrates a secure element embedded in an ID card

FIG. 4 illustrates a secure element embedded in a wristband

FIG. 5 illustrates more details regarding certain components of a secure illustrated in FIG. 1 of a secure element that is capable of bi-directional communication with a mobile device and transfer of data to a remote server

FIG. 6 illustrates multiple secure elements coupled to a mobile communication device

FIG. 7 illustrates secure element applications

FIG. 8 illustrates medical devices with an externally affixed secure element

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Reference will now be made in detail to various embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present inventions. However, it will be apparent to one of ordinary skill in the art that the present inventions may be practiced without these specific details. In other instances, well-known methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

An NFC enabled device is one that includes a secure element and enables contactless transactions which have been described in more detail in previous patents including U.S. patent application Ser. No. 13/184,246, entitled "Using a mobile device to enable purchase of deals and increase customer loyalty" filed on Jul. 15, 2011, U.S. Provisional Patent Application No. 61/445,667, entitled "Non-Wireless Bidirectional Communication Between a Mobile Device and Associated Secure Element using an Audio Port" filed on Feb. 23, 2011 and U.S. Provisional Patent Application No. 61/429,246, entitled "Wireless Bidirectional Communications between a Mobile Device and Associated Secure Element using Inaudible Sound Waves," filed Jan. 3, 2011 both of which are a continuation in part of U.S. patent application Ser. No. 12/948,717, entitled "Wireless Bidirectional Communications between a Mobile Device and Associated Secure Element," filed Nov. 17, 2010, U.S. patent application Ser. No. 12/592,581 entitled "Method and Apparatus For Completing A Transaction Using A Wireless Mobile Communication Channel and Another Communication Channel", filed Nov. 25, 2009, U.S. patent application Ser. No. 11/948,903, entitled "Method And System For Conducting An Online Payment Transaction Using A Mobile Communication Device" filed on Nov. 30, 2007, U.S. patent application Ser. No. 11/939,821, entitled "Method and System for Securing Transactions Made Through a Mobile Communication Device" filed Nov. 14, 2007, and U.S. patent application Ser. No. 11/933,351 entitled "Method and System for Purchasing Event Tickets Using a Mobile Communication Device", filed Oct. 31, 2007, and U.S. patent application Ser. No. 11/933,321 entitled "Method and System for Adapting a Wireless Mobile Communication Device for Wireless Transactions,"

6

filed Oct. 31, 2007 all of which are a continuation-in-part of U.S. patent application Ser. No. 11/467,441, entitled "Method and Apparatus for Completing a Transaction Using a Wireless Mobile Communication Channel and Another Communication Channel," filed Aug. 25, 2006, which claims priority to U.S. Provisional Patent Application Nos. 60/766,171 and 60/766,172, both of which were filed Dec. 31, 2005. All of the above-referenced patent applications are incorporated by reference herein in their entirety.

As previously described in U.S. patent application Ser. No. 12/592,581, entitled "Method and Apparatus For Completing A Transaction Using A Wireless Mobile Communication Channel and Another Communication Channel", filed Nov. 25, 2009 which is a continuation in part of U.S. patent application Ser. No. 11/467,441, entitled "Method and Apparatus For Completing A Transaction Using A Wireless Mobile Communication Channel and Another Communication Channel", filed Aug. 25, 2006, FIG. 1 is a block diagram illustrating a communication system 100 in accordance with some embodiments. The communication system 100 includes a hand-held, wireless mobile communication device 110 with an antenna 120 for wireless communication. While the antenna 120 is shown as extending from the mobile communication device 110 for visual clarity, the antenna 120 may be implemented internally within the mobile communication device 110. Also, the mobile communication device 110 may include more than one antenna 120. The mobile communication device 110 includes a user interface for entering data. For example, a display 124 (FIG. 2) is a touch-screen display; alternatively or in addition, the mobile communication device 110 includes a keypad 125 (FIG. 2) for entering data.

A preferred embodiment, both the radio element 120 and the secure element 130 are both disposed internally within a body of the mobile device 110 as illustrated in FIG. 1, although in certain embodiments the secure element 130 can be external to the mobile device 110 as described hereinafter. In a variant implementation, the mobile device 110 contain a slot, which allows for the insertion of a secure element 130 into a slot and thus the physical insertion, mechanical and electrical connection as needed. In this configuration, the secure element can be purchased independently of the mobile device 110. The secure element 130 can also be disposed into a slot that only provides for physical insertion and mechanical connection to the body of the mobile device 110, and can then preferably include a transceiver that allows for the communication with the radio element 130 using a wireless local communication channel.

The radio element 120 also is illustrated as optionally including another transceiver 129, such as a Bluetooth or WIFI transceiver, which can transmit and receive signals with an external device and then communicate signals to and from the radio processor 123. This additional communication channel allows for communications between other external devices, such as an external Bluetooth enabled smartcard, and provides an additional communication channel that is useful for certain transactions, as described further herein.

FIG. 2B1 illustrates a preferred embodiment of the secure element 130 associated with the mobile device 110, the secure element 130 being commonly known as a smart card. As illustrated, the secure element 130 has a secure processor 132, a secure memory 133 and a POS/NFC transceiver 134 adapted to send transaction request signals and receive transaction response signals over a first communication channel. The secure processor 132 communicates via the secure element driver 128 with the radio processor 123,

using, as mentioned above, signals described in the Java Card 2.1 Platform API Specification. The transaction request signals and the transaction response signals associated with the transaction preferably include identification code associated with the user, as well as information relative to the transaction, such as item, quantity, vendor, as is known. The POS transceiver **134** is preferably an NFC device of some type, which uses an NFC modem, although it can also be a Bluetooth, WIFI or other transceiver. In the case of the implementation of the POS transceiver being an NFC modem, such an NFC modem will typically have a set of registers that can be read/written by the secure processor **132**. These registers are in turn available for reading and writing over the RFID communications channel and serve as a sort of shared memory between the secure processor **123** within the secure element **130** and the RFID reader that is associated with the POS terminal **150**. This communication is specified, for example, in the ISO 14443A/B standard and ISO 15693 just to name a few.

Illustrated in an alternative embodiment is the inclusion of a radio/Bluetooth/WIFI transceiver **136**, which can communicate with other devices, such as a transceiver associated with the radio processor **120** or for other external devices having those communication capabilities, thus allowing for more flexibility.

FIG. 2B2A shows a modified secure element **130**, in which the radio element **120** does not communicate with the secure element through a secure element driver **128** of some type. In this case, for example, the secure element **130** may be external to the mobile device **110** and as such is not connected to the radio element through the secure element driver **128**. In such an implementation, however, if the transceiver **136** as described above is included, and a similar transceiver **129** associated with the radio element **130** as described previously with respect to FIG. 1 is included, then this communication channel can be used to wirelessly obtain direct communications between the radio element **120** and the secure element **130**.

This implementation allows for certain bidirectional communications with other devices, as well as with the radio element **120**, and as such more functionality and flexibility is achieved. This implementation is particularly useful since it establishes a direct local communication path with the radio element **120**, since there is not communications with the radio element **120** via the path of driver **128**.

If either of the transceivers **129** or **136** are not associated with the respective radio element **120** or secure element **130**, and there is no direct connection between the radio element **120** and the secure element **130**, then a direct communication link between the radio element **120** and the secure element **130** will not exist. As such, while ticketing and many transactions can still exist, data from a real-time transaction performed using the secure element **130** cannot be made directly available to the radio processor and the applications stored thereon, which can prevent, for example, certain redundancy checks to occur, such as a ticketing application in which, after the ticket order has been placed, the ticketing application in the memory **126** associated with the radio element **130** can be programmed to provide an alert if the ticket receipt, via the management server **180**, has not been received within a certain period of time. Such an alert would not be possible to program directly (although it could be programmed indirectly via the button panel on the phone, though such an implementation requires extra user intervention, which, if possible, one attempts to avoid in transactions such as this.

FIG. 2B2B shows a modified secure element **130'**, in which the secure element does not include a processor that is capable of bidirectional communications, but instead is a passive device **138'**, such as an RFID sticker or some other tag, that allows for a user identification, such that a transaction that is initiated with the passive device **138'** will cause the management server **180** to perform the transaction details. In this implementation, the code received from the POS terminal **150** or the POE terminal **190** is transmitted from the POS terminal **150** or the POE terminal **190** to the management server **180**, which then takes over the transaction. This passive device **138'**, with the identification code stored thereon, can thus be associated with a mobile device **110** not otherwise equipped for such communications, and the management server **190** can provide transactional information to the mobile device **110** using available channels on the mobile device (such as audio, sms or other known data transmission methods). While bidirectional communications do not occur with other devices, transactions are possible, because the management server **190** is involved.

FIG. 2B2C illustrates a secure element that is capable of either two-way communication or one-way communication with a POS/POE device that is not affixed to a mobile device nor electrically coupled to the mobile device. Instead the secure element is affixed to a hospital bracelet. FIG. 3 illustrates a secure element that is affixed to a affixed to a plastic medical ID card and FIG. 4 illustrates a secure element affixed to a affixed to a hospital bracelet, for example. Similarly, a secure element that is not affixed to a mobile device nor is electrically coupled to a mobile device can be incorporated with a key chain, watch, ring, bracelet worn as jewelry.

As illustrated in FIG. 5, and enhanced secure element **130** that is capable of bidirectional communication with a mobile device has a secure NFC processor **132**, a secure memory **133** and a POS/NFC transceiver **134** adapted to send transaction request signals and receive transaction response signals over a first communication channel. A/D converter **135**, a microphone **137**, a speaker **139**, and a, cable **141**, power harvester, **144**, Long range RF transceiver, **146**, and a SE controller, **148**. The Secure Element Controller **148** can either be logical or physical. In a logical implementation, it simply utilizes the primary secure element transceiver **134**, memory **133** with data and applications, and a processor **132** to communicate with multiple logical or physical secure elements. Stated another way, the Secure Element Controller is the parent controller and all of the other logical or physical secure elements. The Secure Element Controller can issue read/write commands to all of the other logical or physical secure elements.

As described above, the secure element **130** has a secure processor **132**, a secure memory **133** and a POS or NFC transceiver **134** adapted to send transaction request signals and receive transaction response signals over a first communication channel. In some embodiments a secure element **130** is internal to the mobile communication device **110**. In some embodiments, the secure element **130** is externally attached to the mobile communication device **110**. For example, the secure element **130** is adhesively affixed or mechanically secured to the housing of the mobile communication device **110**. Alternatively, the secure element **130** is housed within a slot in the mobile communication device **110**. The secure element **130** includes an antenna **131** for wireless communication. While the antenna **131** is shown as extending from the secure element **130** for visual clarity, the antenna **131** may be implemented internally within the secure element **130**. Also, the secure element **130** may

include more than one antenna **131**. Communication occurs wirelessly between the secure element **130** and the mobile communication device **110** via respective antennas **120** and **131**, over a direct wireless channel **163** between the mobile communication device **110** and the secure element **130**. Thus, in some embodiments, the channel **163** does not pass through a network.

The point of sale terminal **150** illustrated in FIG. **1** is conventional, in that it has the capability of electronically reading information from a device equipped to transmit information in a format that it reads. Thus, the reader (not shown) within the point of sale terminal **150** can be of one or many types. If the point of sale terminal reader (not shown) includes the provision for NFC communications, then simply bringing the secure element **130** with the NFC transceiver will cause initiation of a transaction and the transmission of the identification code associated with the secure element **130** and thus the user.

For the embodiments described above, various software that is downloaded into the memory **126** of the radio element **120** and the secure memory **132** of the secure element **130**, along with software resident on the management server **180**, will cooperate at a layer that is above the physical layer of the communications, in order for the desired transaction to occur. This software is implemented using based upon known knowledge of mobile device **110** internals and application platforms, NFC, smartcard internals and application platforms, payment protocols (e.g. PayPass), and the working/workflow associated with POS and POE terminals, and the transaction and management servers. In addition, the present invention provides for piggybacking a tunneling protocol on top of the payment protocol, so that the secure elements **130** can communicate with the transaction server **170** and/or the management server **180**, without modification to the POS terminal **150** or the POE terminal **190**. As such, this includes software within the secure element **130** that embeds the required information in fields which will not adversely affect the performance of the POS terminal **150** and/or the POE terminal **190**, and also software in transaction server **170** that will extract the piggybacked payload, associate the payload with the management server **180** if needed, and then authenticate, authorize, and execute transfers of transaction information to the management server **180**.

In another embodiment, the piggybacked payload is sent, instead of to the transaction server **170**, to the management server **180**, which can then associate the transaction and notify the transaction server **170**, the POS terminal **150** and/or the POE terminal as needed.

There are several types of NFC transactions. First, when the secure element is held in proximity to a remote device (i.e. Point-Of-Sale (POS) device **150**, Point-Of-Entry (POE) **190**, Point-Of-Presence (POP) device **200**, smart poster, another secure element, etc) the POS/POE/POP activates or powers the secure element **130** through induction and triggers an application residing in the secure element (which is different than an application residing on the mobile communication device. So, the secure element need not have its own power source nor does the secure element require use of the battery inside of the mobile device. Stated another way, if the battery in the mobile device is dead, the user may not be able to use the mobile device to place a phone call, receive an SMS, or surf the web, but they will be able to purchase item and receive coupons and other digital artifacts using the secure element since the secure element is powered by the remote NFC enabled POS/POE/POP device. To reiterate, after triggering the secure element, an application

residing in the secure element (which is different than an application residing on the mobile communication device) is launched and the application can transfer digital artifacts to the POS/POE/POP and the POS/POE/POP terminal can transmit digital artifacts to the secure element again even if the battery inside of the mobile communication device lacks power. There are instances when the NFC enabled mobile device is active and it can power any NFC device in passive mode including a POS/POE/POP, smart poster, or another NFC enabled mobile device which will be described in more detail further herein.

While a POS may receive payment credentials from the secure element which is processed by the transaction server **170**, the POS may transfer a coupon, receipt, or some other digital artifact to the secure element simultaneously during the induction process from the POS terminal **150**, the transaction server **170** or the management server **180**. Stated another way, the user need only hold, “wave” or “tap” their NFC enabled device once near the POS and both the transmission of the ticket to the POP and the receipt of the digital artifact will occur simultaneously so the user will not have to “tap” or “wave” their phone twice. This is accomplished through induction as well. The POS device/terminal will activate the secure element and an application residing in the secure element (which is different than an application residing on the mobile communication device) will facilitate the transfer.

As mentioned previously a Point-Of-Entry (POE) terminal is also equipped with NFC. When a user holds, “waves”, or “taps” their NFC enabled device near a POE terminal, the POE terminal activates the secure element in the NFC enabled mobile device and triggers an application in the secure element to transfer a ticket, for example, to the POE device which enables the user to gain access to the venue, building, automobile, etc.

While an NFC enabled Point of Sale (POS) facilitates a contactless purchase or financial transaction and a Point-of-Entry (POE) terminal facilitates contactless access, an NFC enabled Point of Presence (POP) facilitates contactless transaction. A POP device is similar to an NFC POS enabled device in that it does contain a secure element and is capable of NFC communications (including two way communications). A POP is also capable of induction to be able to power an NFC enabled mobile communication device held in proximity to it and triggers an application running in the secure element to transfer information from the NFC enabled mobile communication device to the POP. Some examples of POPs include a kiosk, automobile, hotel, house, smart poster, smart catalogue, computer, medical device, another NFC mobile device, a music player, products at a retail store, etc. One example is a user holds their NFC enabled device near a kiosk which powers the secure element and launches an application to transmit a free song from the kiosk to the secure element. The POP can send/receive transaction data to the management server, **180**, have transactions processed by the transaction server **170**, or transfer/receive digital artifacts to/from the secure element **130** at the remote server **210**.

A POP may be a Smart Poster—When an NFC enabled mobile communication device is held in proximity to a smart poster, the smart poster may transmit information, data, maps, or any other type of digital artifact to the secure element.

A POP may be a computer, laptop, tablet, etc. A user first uses the mobile wallet to select which items to be transferred to the POP and instructs the user to hold the NFC device near the POP. When an NFC enabled mobile communication

device is held in proximity to the computer, the computer can transmit information, data, maps, or any other type of digital artifact to the secure element

A POP may be another NFC Enabled Mobile communication device. A user first uses the mobile wallet to select which items to be transferred to the POP and instructs the user to hold the NFC device near the POP. When an NFC enabled mobile communication device is held in proximity to another NFC enabled device may transmit contact information, email, web site addresses, social media information, tickets, coupons, receipts, vouchers, content, or any other type of digital artifact to the secure element

As described in U.S. patent application Ser. No. 13/213,840 entitled "Transferring Data Between NFC Enabled Mobile Devices With Multiple Secure Elements" filed on Aug. 19, 2011 which is incorporated herein by reference, after a user holds an NFC enabled mobile device in proximity to an NFC POS/POE/POP, the NFC POS/POE/POP can transfer secondary digital artifacts to the secure element such as Xrays, tickets, business cards, music, product information, etc. As described in more detail in the patent applications mentioned above, a user may have to authenticate and the secure element may have to be unlocked prior to the storage of digital artifacts in the secure element. For security purposes, the secure element keys are located at the management server, **180** and may be managed by an entity sometimes referred to as a "Trusted Server Manager". In cases where network availability is not reliable and performance is critical, the secure element key may be downloaded to the mobile device in an encrypted file. This communication is specified, for example, in the ISO 14443A/B standard and ISO 15693 just to name a few

As mentioned previously, an NFC enabled mobile communication device may have multiple secure elements. There may be a secure element may be dedicated to specific financial transactions vs another secure element which may be dedicated to medical records and have a separate secure element key. There may even be a secure element that is "public domain" which any POS or device can write to without any restricted accesses. As shown in FIG. 7, there can be a different "health care secure element software application; for different functions. There may be 1 logical secure element or multiple secure elements as described in U.S. patent application Ser. No. 13/213,840, entitled "Transferring Data Between NFC Enabled Mobile Devices With Multiple Secure Elements" filed on Aug. 19, 2011. There may be a secure element and application for prescriptions, office visits, appointments, EMR, pictures, etc. A user may only need to tap once to transfer artifacts to multiple secure elements. Alternatively, a user may tap once to transfer an ID, for example, from the secure element to the POP and then tap another time to transfer artifacts from the POP such as a prescription from the POP to the secure element. The transfer of digital artifacts between secure element and a POP is a result each application stored in the secure element having its own Id. So for example, a secure element application that facilitates transfer of a patient's medical ID to/from a secure element may have an ID of "SE_App1. In contrast, a secure element application that facilitates transfer of prescriptions to/from a secure element may have an ID of "SE_App3". Whenever multiple applications exist in the secure element, the applications must be prioritized so that the POP/POS/POE will know which application to trigger and in which order. So, for example if the user selects to get a prescription using their mobile wallet, the mobile wallet will transfer a signal to the secure element to make the "X ray secure element application or SE_App3" the active one

and assign it priority of 1 so that the POP/POS/POE will select it first. The mobile wallet communicates to the secure element in a number of different ways regardless of whether secure element is internal, inserted into a slot within the body of the mobile device, or affixed externally to the body of a mobile device as described in U.S. Provisional Patent Application No. 61/445,667, entitled "Non-Wireless Bidirectional Communication Between a Mobile Device and Associated Secure Element using an Audio Port" filed on Feb. 23, 2011 and U.S. Provisional Patent Application No. 61/429,246, entitled "Wireless Bidirectional Communications between a Mobile Device and Associated Secure Element using Inaudible Sound Waves," filed Jan. 3, 2011 both of which are a continuation in part of U.S. patent application Ser. No. 12/948,717, entitled "Wireless Bidirectional Communications between a Mobile Device and Associated Secure Element," filed Nov. 17, 2010 which are incorporated by reference herein

In one embodiment, a POP **200** (i.e. medical device) can include secure element that is pre-installed or embedded in the medical device for a wired connection (e.g. USB or serial) or a wireless connection (e.g. NFC, Bluetooth, WIFI, infrared, inaudible sound waves using a speaker and microphone, etc). In this way, the data from the medical can be transmitted to the mobile device **110** coupled to (e.g. the patient's mobile device), another mobile device **210** (e.g. the physician's mobile device), server **170**, POS **150**, POE **190**, another POP **200** (e.g. medical, EMR) using USB, Serial Port, NFC, WIFI, Bluetooth, Infrared, inaudible sound as described in US patent application Non-Wireless Bidirectional Communication Between a Mobile Device and Associated Secure Element using an Audio Port" filed on Feb. 23, 2011, U.S. patent application Ser. No. 13/223,233, "Using an NFC Enabled Mobile Device To Manage Health Care" filed on Aug. 31, 2011" and U.S. patent application Ser. No. 13/218,879 entitled "Using an NFC Enabled Mobile Device To Manage Digital Medical Artifacts" filed on Aug. 26, 2011.

In another embodiment, the POP **200** (i.e. medical device) may be connected to an externally coupled secure element through a "universal health port" **144** is installed on the medical device using a wired connection such as USB, serial port, or audio port as described in US patent application Non-Wireless Bidirectional Communication Between a Mobile Device and Associated Secure Element using an Audio Port" filed on Feb. 23, 2011.

Alternatively, the POP **200** (i.e. medical device) may be connected to an externally coupled secure element through the universal health port using a wireless connection (e.g. NFC, Bluetooth, WIFI, infrared, inaudible sound waves using a speaker and microphone, etc). as described in U.S. Provisional Patent Application No. 61/429,246, entitled "Wireless Bidirectional Communications between a Mobile Device and Associated Secure Element using Inaudible Sound Waves," filed Jan. 3, 2011 both of which are a continuation in part of U.S. patent application Ser. No. 12/948,717, entitled "Wireless Bidirectional Communications between a Mobile Device and Associated Secure Element," filed Nov. 17, 2010, or some other conventional port. The secure element can include WIFI, NFC, Bluetooth, infrared, inaudible sound waves using a speaker and microphone as described in US patent application number, or a combination of these.

In either case regardless of whether the POP, **200** (i.e. medical device) has an embedded secure element or a coupled secure element connected to the universal health port using a wired connection or a wireless connection,

data/digital artifacts can be transferred from the medical device to the secure element using any number of conventional protocols such as USB, Serial Port, NFC, WIFI, Bluetooth, Infrared, inaudible sound waves, etc. Once the data/digital artifacts are at the secure element, they can be transferred from the secure element to the mobile device **110** coupled to (e.g. the patients mobile device), another mobile device **210** (e.g. the physicians mobile device), server **170**, POS **150**, POE **190**, another POP **200** (e.g. medical, EMR) using USB, Serial Port, NFC, WIFI, Bluetooth, Infrared, inaudible sound as described in U.S. patent application Non-Wireless Bidirectional Communication Between a Mobile Device and Associated Secure Element using an Audio Port" filed on Feb. 23, 2011, U.S. patent application Ser. No. 13/223,233, "Using an NFC Enabled Mobile Device To Manage Health Care" filed on Aug. 31, 2011" and U.S. patent application Ser. No. 13/218,879 entitled "Using an NFC Enabled Mobile Device To Manage Digital Medical Artifacts" filed on Aug. 26, 2011.

After the mobile device receives the data/digital artifacts, it can be displayed in the mobile device **110** or the remote mobile device **210** and/or transmitted to another mobile device (e.g. the patients mobile device, the health care provider's mobile device, server), server, Electronic Medical Records, tablet, another medical device, etc as depicted in FIG. 8.

In one embodiment, when a Health Care Provider wants to extract data from a medical device using NFC, the health care providers NFC enabled mobile device (i.e. mobile device with embedded NFC, NFC in a slot, NFC smart sicker) powers or activates the secure element application located inside the secure element of the medical device which has either an embedded NFC or externally coupled secure element. In doing so, the medical device secure element application transfers data to the health care providers NFC enabled mobile device as described in U.S. patent application Ser. No. 13/223,233, "Using an NFC Enabled Mobile Device To Manage Health Care" filed on Aug. 31, 2011" and U.S. patent application Ser. No. 13/218,879 entitled "Using an NFC Enabled Mobile Device To Manage Digital Medical Artifacts" filed on Aug. 26, 2011.

In another embodiment, the Health Care Provider's mobile device simply has a secure element with only an NFC transceiver. When a Health Care Provider wants to extract data from a medical device with the secure element coupled to it, the health care provider "waves" or "holds" their mobile device which only has an NFC transceiver near the medical device with the coupled secure element. In doing so, the secure element coupled to the medical device activates an application running on the health care provider mobile device (not the secure element) which subsequently connects to an application on a remote server for processing. Alternatively, the NFC transceiver may simply execute an application stored on a remote server bypassing an application on the mobile device. In this way, the health care provider's mobile device need not have a full secure element with its own memory and a secure element application. Stated another way, the NFC transceiver in the Health Care Provider's mobile device is simply used as a trigger to execute an application either stored on the mobile device and/or stored on a server when it is brought into proximity of a medical device which has a secure element to trigger the NFC transceiver via NFC induction. This approach enables the health care provider to utilize applications stored on the management server which is more scalable since the applications that reside on a server can be easily added, changed, etc.

For example, if the Health Care Provider (HCP) wishes to update a patients EMR records stored at the server with the data from the medical device, the Health Care Provider waves their mobile device near the medical device with the coupled secure element and upon doing so, the EMR application on the Health Care Provider mobile device launches and connects to the EMR application on the server to automatically transfer the measurement/sensor data from the medical device to the HCP mobile device and to the server using conventional wireless service.

In cases where security is required to capture and transfer the data, the techniques described as described in U.S. patent application Ser. No. 13/223,233, entitled "Using an NFC Enabled Mobile Device To Manage Health Care" filed on Aug. 31, 2011" and U.S. patent application Ser. No. 13/218,879 entitled "Using an NFC Enabled Mobile Device To Manage Digital Medical Artifacts" filed on Aug. 26, 2011.

In some embodiments, digital artifacts can be removed from the secure element coupled to the medical device as described in U as described in U.S. patent application Ser. No. 13/223,233, entitled, "Using an NFC Enabled Mobile Device To Manage Health Care" filed on Aug. 31, 2011" and U.S. patent application Ser. No. 13/218,879 entitled "Using an NFC Enabled Mobile Device To Manage Digital Medical Artifacts" filed on Aug. 26, 2011.

In some embodiments, the mobile wallet which is running on the mobile device/smart phone displays data transmitted from the medical device can include digital artifacts as described in U.S. patent application Ser. No. 11/956,261 entitled "Method and System for Delivering Customized Information To A Mobile Communication Device Based on User Affiliations", filed Dec. 13, 2007

What is claimed is:

1. A method for transmitting a medical digital artifact from a mobile device, the method comprising:

executing a first secure element application on a processor of a first secure element coupled to a medical device externally coupled to a body in response to a Near Field Communication (NFC) inductive signal by a second secure element coupled to the mobile device, wherein the first secure element is connected to the medical device via a universal port, the first secure element application configured to use a near field communication protocol;

wirelessly transmitting the medical digital artifact from first secure element coupled to the medical device using the first secure element application, through a first communication channel configured to use the NFC protocol to the second secure element coupled to the mobile device and further wherein the mobile device wirelessly transmits the medical digital artifact using a non-browser based mobile application to a server for processing through a second communication channel, wherein the second communication channel is different than the first communication channel, wherein the non-browser based mobile application is a mobile operating system platform non-browser based mobile application with a graphical user interface that is pre-installed or downloaded and installed on the mobile device, wherein the graphical user interface includes a graphical icon;

receiving response data at the non-browser based mobile application running on the mobile device from the sever through the second communication channel for display within the non-browser based mobile application running on the mobile device, wherein the mobile device comprises a mobile device transceiver, a mobile

15

device display, and a mobile device memory for storing the non-browser based mobile application.

2. The method of claim 1, wherein the first secure element is coupled to the universal port using a Universal Serial Bus (USB).

3. The method of claim 1, wherein the first secure element is coupled to the universal port using a wireless connection.

4. The method of claim 3, wherein the wireless connection is NFC.

5. The method of claim 3, wherein the wireless connection is Bluetooth.

6. The method of claim 3, wherein the wireless connection is inaudible sound waves.

7. The method of claim 3, wherein the wireless connection is WIFI.

8. The method of claim 1, further wherein the medical digital artifacts is stored in a secure element memory different than a secure element memory that the secure application is stored in.

9. The method of claim 1, wherein different secure element applications are stored in different secure elements, and further wherein a secure element controller manages the different secure element applications.

10. The method of claim 1, wherein the medical digital artifact comprises one or more of information related to a medical id, information related to patient information, information related to a prescription, information related to emergency contact information, information related to physician information, information related to a vital signs, information related to insurance information, information related to an office visit summary, information related to an appointment, information related to an Electronic Medical Records (EMR), information related to a lab result, information related to blood type, information related to organ/donor status, information related to diagnostic data, or information related to an immunization record.

11. The method of claim 10, wherein patient information includes one or more of information related to gender, information related to age, information related to date of birth, information related to blood type, information related to race, information related to contact lenses, information related to an implant, or information related to a pacemaker.

12. The method of claim 10, wherein the vital sign includes one or more of information related to temperature, information related to blood pressure, information related to pulse, information related to respiratory rate, information related to pain level, information related to glucose level, information related to cholesterol, information related to height, or information related to weight.

13. The method of claim 10, wherein the insurance information includes one or more of information related to a doctor, information related to a lab, information related to a drug, information related to a generic drug, information related to health care coverage, information related to out of pocket costs, or information related to co-pay costs.

14. The method of claim 1, further wherein the medical digital artifact can be viewed using the non-browser based application when the mobile device is not connected to a network.

15. The method of claim 1, wherein the medical device comprises a blood glucose machine, blood pressure machine, scale, inhaler, medical ID, or hospital bracelet.

16. The method of claim 1, further wherein the medical digital artifact stored on the mobile device is encrypted using a mobile operating system native to the mobile device.

17. The method of claim 1, further wherein upon the condition that the mobile device loses connection with a

16

wireless network, the non-browser based mobile application monitors for access to the wireless network and automatically reconnects to the wireless network when the wireless network is available.

18. The method of claim 1, further wherein the non-browser based mobile application sends an alert if it has not received the medical digital artifact within a certain period of time.

19. The method of claim 1, wherein the server is configured to store a single identification code for the user for a plurality of the user's mobile devices.

20. The method of claim 1, wherein the response data comprises one or more of a transaction number, receipt, content, or a coupon.

21. A system for transmitting a medical digital artifact from a mobile device, the system comprising:

a secure element processor executing a first secure element application, in response to a Near Field Communication (NFC) inductive signal by the second secure element coupled to a mobile device wherein the first secure element is coupled to the a medical device using a universal port, the first secure element application configured to use a near field communication protocol, the medical device is externally coupled to a body;

a secure element transceiver for wirelessly transmitting the medical digital artifact associated with the executed first secure element application, through a first communication channel configured to use the NFC protocol to the second secure element coupled to the mobile device and further wherein the mobile device sends the medical digital artifact to a server for processing through a second communication channel, wherein the second communication channel is different than the first communication channel;

a mobile device transceiver for receiving, at a non-browser base mobile application, response data from the sever through the second communication channel and further wherein the response data is displayed within the non-browser based mobile application, wherein the mobile device comprises a mobile device transceiver, a mobile device display, and a mobile device memory for storing the non-browser based mobile application, wherein the non-browser based mobile application is a mobile operating system platform non-browser based mobile application with a graphical user interface that is preinstalled or downloaded and installed on the mobile device wherein the graphical user interface includes a graphical icon.

22. The system of claim 21 wherein the first secure element is coupled to the universal port using a Universal Serial Bus (USB).

23. The system of claim 21 wherein the first secure element is coupled to the universal port using a wireless connection.

24. The system of claim 23, wherein the wireless connection is NFC.

25. The system of claim 23, wherein the wireless connection is Bluetooth.

26. The system of claim 23, further wherein the medical digital artifacts is stored in a secure element memory different than a secure element memory that the secure application is stored in.

27. The system of claim 23, wherein the wireless connection is WIFI.

28. The system of claim 23, further wherein upon the condition that the mobile device loses connection with a wireless network, the non-browser based mobile application

monitors for access to the wireless network and automatically reconnects to the wireless network when the wireless network is available.

29. The system of claim 23, further wherein the non-browser based mobile application sends an alert if it has not received the medical digital artifact within a certain period of time.

30. The system of claim 23, wherein the server is configured to store a single identification code for the user for a plurality of the user's mobile devices.

31. The system of claim 23, wherein the response data comprises one or more of a transaction number, receipt, content, or a coupon.

32. The system of claim 21, wherein different secure element applications are stored in different secure elements, and further wherein a secure element controller manages the different secure element applications.

33. The system of claim 21, wherein the medical digital artifact-comprises one or more of information related to a medical id, information related to patient information, information related to a prescription, information related to emergency contact information, information related to physician information, information related to a vital signs, information related to insurance information, information related to an office visit summary, information related to an appointment, information related to an Electronic Medical Records (EMR), information related to a lab result, information related to blood type, information related to organ/donor status, information related to diagnostic data, or information related to an immunization record.

34. The system of claim 33, wherein the patient information includes one or more of information related to gender, information related to age, information related to date of birth, information related to blood type, information related to race, information related to contact lenses, information related to an implant, or information related to a pacemaker.

35. The system of claim 33, wherein the vital sign includes one or more of information related to temperature, information related to blood pressure, information related to pulse, information related to respiratory rate, information related to pain level, information related to glucose level, information related to cholesterol, information related to height, or information related to weight.

36. The system of claim 33, wherein insurance information includes one or more of information related to a doctor, information related to a lab, information related to a drug, information related to a generic drug, information related to health care coverage, information related to out of pocket costs, or information related to co-pay costs.

37. The system of claim 21, further wherein the medical digital artifact can be viewed using the non-browser based application when the mobile device is not connected to a network.

38. The system of claim 21, wherein the medical device comprises a blood glucose machine, blood pressure machine, scale, inhaler, medical ID, or hospital bracelet.

39. The system of claim 21, further wherein the medical digital artifact stored on the mobile device is encrypted using a mobile operating system native to the mobile device.

* * * * *